



Specifications Ledvance LED  
Floodlight Flex White 250W 37500lm  
60D - 830 Warm White | IP66 - Dali  
Dimmable - Symmetrical



[View Product](#)

General Information

|                          |                                                           |
|--------------------------|-----------------------------------------------------------|
| SKU                      | 252385                                                    |
| EAN                      | 4099854373749                                             |
| Brand                    | Ledvance                                                  |
| Manufacturer Name        | FLOODLIGHT FLEX DALI RADIAL SYMMETRIC 60 250W 830 R60 WAL |
| Any Lamp all-in warranty | 5 Years                                                   |
| Average Lifetime (h)     | 120000                                                    |

Technical Information

|                             |                    |
|-----------------------------|--------------------|
| Technology                  | LED Integrated     |
| Wattage                     | 250                |
| Replaces (Watt)             | 200                |
| Voltage (V)                 | 220-240            |
| Dimmable                    | Dimmable with Dali |
| Colour Code                 | 830 Warm White     |
| Colour temperature (Kelvin) | 3000 Warm White    |
| Colour Rendering (Ra)       | 80-89              |
| Colour of Light             | White              |
| Light colour options        | Single Color       |
| Luminous Flux (Lumen)       | 37500              |
| Luminous Efficacy (lm/W)    | 150                |

|                       |                |
|-----------------------|----------------|
| Beam Angle (degree)   | 60             |
| Power factor          | >0.96          |
| Product Type Category | LED Floodlight |

## Fixture Information

|                        |                    |
|------------------------|--------------------|
| Mounting Method        | Surface            |
| Fixture Connection     | Screwless terminal |
| Light Distribution     | Symmetrical        |
| IP-rating              | IP66               |
| Impact Protection (IK) | IK08 - 5 joules    |
| Operating Temperature  | -30 to +50         |
| Colour of the Fixture  | White              |
| Housing                | Aluminium          |
| Colour of material     | White              |
| Emergency Lighting     | No Emergency Unit  |

## Dimensions

|             |     |
|-------------|-----|
| Length (mm) | 627 |
| Width (mm)  | 416 |
| Height (mm) | 68  |

## Sensor Information

Type of sensor

**Why Any-lamp?**  
No Sensor



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process