



Specifications Ledvance LED  
Downlight Comfort Opal White 18W  
/15W/12W - 2160lm/1800lm/1440lm  
95D -9830-940 CCT | Cutout 150mm -  
IP44

[View Product](#)

General Information

|                          |                                      |
|--------------------------|--------------------------------------|
| SKU                      | 254956                               |
| EAN                      | 4099854490941                        |
| Brand                    | Ledvance                             |
| Manufacturer Name        | DL CMFT D150 P 18W MS 940 OP WT LEDV |
| Any Lamp all-in warranty | 5 Years                              |
| Average Lifetime (h)     | 100000                               |

Technical Information

|                             |                                                |
|-----------------------------|------------------------------------------------|
| Emergency Lighting          | No Emergency Unit                              |
| Tiltable                    | No                                             |
| Technology                  | LED Integrated                                 |
| Replaces (Watt)             | 2x18                                           |
| Wattage                     | 18                                             |
| Voltage (V)                 | 220-240                                        |
| Dimmable                    | Not Dimmable                                   |
| Colour Code                 | 930 Warm White, 940 Cool White, 840 Cool White |
| Colour temperature (Kelvin) | 3000 Warm White, 4000 Cool White               |
| Colour Rendering (Ra)       | 90-99                                          |
| Colour of Light             | White                                          |
| Light colour options        | CCT                                            |

|                          |                          |
|--------------------------|--------------------------|
| Beam Angle (degree)      | 95                       |
| Luminous Flux (Lumen)    | 2160                     |
| Luminous Efficacy (lm/W) | 120                      |
| Power factor             | >0.90                    |
| Unified Glare Rating     | < 23 - for general areas |
| Optical Cover            | Opal                     |
| Product Type Category    | LED Downlight            |

## Fixture Information

|                        |                        |
|------------------------|------------------------|
| Mounting Method        | Recessed               |
| Cut out (mm)           | 150                    |
| IP-rating              | IP44                   |
| Impact Protection (IK) | IK03 - 0.35 joule      |
| Operating Temperature  | -20 to +40             |
| Housing                | Aluminium              |
| Colour of the Fixture  | White                  |
| Fixture Connection     | PI [Push-in connector] |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 57  |
| Diameter (mm) | 160 |

## Sensor Information

Type of sensor No Sensor



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process